

DETAILED LOG

Hole Number: ER08-52

Units: METRIC

Project Name: Norway - South Norway	Primary Coordinates Grid: UTM84-32N	Destination Coordinates Grid: UTM:	Collar Dip: -51.90
Project Number: 203	North: 6659476.29	North: 60.07	Collar Az: 55.00
Location: Ertelia Mine	East: 558343.98	East: 10.05	Length: 92.66 (m)
	Elev: 156.14	Elev: 156.14	Start Depth: 0.00 (m)
Date Started: Feb 18, 2008	Collar Survey: N	Plugged: N	Contractor: Drillcon Core AB
Date Completed: Feb 23, 2008	Multishot Survey: N	Hole Size: BQ	Core Storage: Tyrstrand
Logged By: klnor	Pulse EM Survey: N	Casing: Left in Hole	Final Depth: 92.66 (m)

Comments: TARGET: GAB/FW btw ER08-51 and surface at vertical depth of 100m.

RESULTS: Collared and remained in FOOTWALL rocks. Hole abandoned in prominent FAULT / GOUGE ZONE. Contractor lost reaming shell and drill bit in the hole.

Casing left in hole.

Sample Averages

Survey Data

Depth (m)	Azimuth Decimal	Dip Decimal	Test Type	Flag	Comments	Depth (m)	Azimuth Decimal	Dip Decimal	Test Type	Flag	Comments
10.00		-51.90	EZ	OK		25.00	55.40	-52.00	EZ	OK	
50.00	55.40	-51.80	EZ	OK		75.00	55.50	-51.20	EZ	OK	

Detailed Lithology			Assay Data						
From (m)	To (m)	Lithology	Sample Number	From (m)	To (m)	Length (m)	Ni%	Cu%	Co%
0	13.60	CAS, Casing							
13.60	26.00	PEG, Pegmatite Pegmatite greyish white in colour, pegmatitic texture, pervasively silicified, garnetiferous, locally fractured core, nil sulphide mineralization, broken lower contact.							

Hole Number: ER08-52

Units: METRIC

Detailed Lithology		Lithology	Assay Data						
From (m)	To (m)		Sample Number	From (m)	To (m)	Length (m)	Ni%	Cu%	Co%
26.00	90.30	FGN, Felsic Gneiss Footwall Gneiss grey in colour, fine grained, colour banded, predominately felsic composition, scattered f.g. garnets throughout, fractured core from 26.0 - 36.30m, trace sulphide mineralization. Structure 26.00 - 36.30 strongly fractured and blocky core 45.25 - 45.75 fractured core and minor fissile clay gouge 53.60 - 53.80 blocky, fractured, rubbly core 57.85 - 60.70 strongly fractured, core segments up to 17cm in length. 67.20 - 70.35 strongly fractured core 78.21 - 80.35 healed brecciation and shear banding							
90.30	92.65	FLT, Fault Strong FAULT at 90.30m pervasive gouge and crushed rubbly core.							
92.65	92.66	EOH, End of Hole							